

# WALL2FLOOR

## CLEANING GUIDE

### REGULAR CLEANING | WHEN NEEDED

Clean finishes as needed, be sure to watch out for marks and stains that can lead to further damage. We recommend using a **pH neutral enzyme formula** such as Simply Clean's Floor Cleaner (**never exceed a washing temperature of 40 °C**, avoiding thermal shock and steam cleaning).

It is a good rule to quickly remove aggressive substances and rinse with water to avoid the prolonged contact and the possible corrosion of the surface of Wall2Floor. It is always a good rule to intervene promptly on the surface as soon as soiling is noticed.



The first cleaning operations can be carried out after the curing is complete, generally after **at least 6-7 days**. In general, surfaces coated with the Wall2Floor system can be washed with non-aggressive neutral detergents (similar treatment to timber flooring), in cold or moderately-warm water.



Do not use acidic or acid-buffered de-scaling detergents that are specific for cleaning concrete surfaces.

### MAINTENANCE WAX | EVERY 6 MONTHS

Surfaces decorated with the Wall2Floor system that, over time, have lost some of their initial shine, can be revived by applying Wall2Floor Maintenance Wax, which is a self-polishing liquid wax. Wall2Floor Maintenance Wax creates a glossy sacrificial layer, which helps protect the surface from dirt and scratches from everyday use.

We recommend applying maintenance wax **every 6 months** in high traffic areas of your home. The first maintenance operations can be carried out after the curing is complete, generally after **at least 6-7 days**.

#### Instructions For Use

With the background dry and clean, use a wax spreader or a damp cloth to apply a layer of Wall2Floor Maintenance Wax. Spread the product evenly over the entire surface you are treating.

*In cases of severe damage, we highly recommend to have a technical professional look at your finish. Novacolor Australia cannot guarantee the quality of any repairs undertaken outside of our direct supervision and therefore cannot be held liable for further damages.*

WEBSITE | [www.novacoloraustralia.com.au](http://www.novacoloraustralia.com.au)  
EMAIL | [sales@novacoloraustralia.com.au](mailto:sales@novacoloraustralia.com.au)  
TECHNICAL | 0417 373 089  
ADDRESS | Factory 23/513-515 Maroondah Hwy, Ringwood, VIC

**novacolor**  
Decorative Finishes  
australia | new zealand

